



Additel 160

Intelligent Digital Pressure Modules

- Pressure measurement accuracy of 0.025% FS
- Pressure ranges to 10,000 psi (700 bar)
- Fully temperature compensated accuracy



Gauge pressure Differential pressure

OVERVIEW

With advanced microprocessor technology and state-of-the-art silicon pressure sensors, the Additel 160 series Intelligent Digital Pressure Module (IDPM) provides an accurate, reliable, and economic solution for wide range of pressure applications. It is loaded with functionality and remarkably easy to use. In order to reach the best performance, every silicon pressure sensor in the module has been specially aged, tested and screened before assembly. Designed as external pressure module for Additel 761 automated pressure calibrator and Additel 222A, Additel 223A and Additel 761 calibrators, the Additel 160 IDPM is unmatched in performance and reliability.

FEATURES

- Gauge pressure measurement accuracy of 0.025% FS
Absolute Pressure measurement accuracy of 0.1% FS
- Pressure ranges to 10,000 psi (700 bar)
- Advanced temperature compensation
- NIST traceable calibration and data included

SPECIFICATIONS

- **Gauge types**
Gauge pressure
Compound pressure
Absolute pressure
- **Pressure Ranges and Accuracy**

Compound Pressure					
P/N	Pressure Range		Media	Accuracy(%FS)	Burst Pressure
	(psi)	(bar)			
CP2	±2	±0.16	G	0.05	3x
CP5	±5	±0.35	G	0.05	3x
CP10	±10	±0.7	G	0.05	3x
CP15	±15	±1	G	0.025	3x
CP30	-15 to 30	-1 to 2	G	0.025	3x
CP100	-15 to 100	-1 to 7	G, L	0.025	3x
CP300	-15 to 300	-1 to 20	G, L	0.025	3x

Gauge Pressure ^[1]					
P/N	Pressure Range		Media ^[2]	Accuracy(%FS)	Burst Pressure
	(psi)	(bar)			
V15	-15	-1.0	G	0.025	3x
GP2	2	0.16	G	0.05	3x
GP5	5	0.35	G	0.05	3x
GP10	10	0.7	G	0.05	3x
GP15	15	1.0	G	0.025	3x
GP30	30	2.0	G	0.025	3x
GP50	50	3.5	G, L	0.025	3x
GP100	100	7.0	G, L	0.025	3x
GP300	300	20	G, L	0.025	3x
GP500	500	35	G, L	0.025	3x
GP600	600	40	G, L	0.025	3x
GP1K	1,000	70	G, L	0.025	2x
GP2K	2,000	140	G, L	0.025	3x
GP3K	3,000	200	G, L	0.025	3x
GP5K	5,000	350	G, L	0.025	3x
GP10K	10,000	700	G, L	0.025	2x

Note:

[1]. Sealed gauge pressure for above 1000 psi

[2]. G=Gas, L=Liquid

SPECIFICATIONS

Absolute Pressure					
P/N	Pressure Range		Media	Accuracy(%FS)	Burst Pressure
	(psi)	(bar)			
AP5	5	0.35	G	0.1	3x
AP10	10	0.7	G	0.1	3x
AP15	15	1.0	G	0.1	3x
AP30	30	2.0	G	0.1	3x
AP50	50	3.5	G	0.1	3x
AP100	100	7.0	G , L	0.1	3x
AP300	300	20	G , L	0.1	3x
AP500	500	35	G , L	0.1	3x
AP1K	1,000	70	G , L	0.1	2x
AP3K	3,000	200	G , L	0.1	3x
AP5K	5,000	350	G , L	0.1	3x

Differential Pressure					
P/N	Pressure Range		Media	Accuracy(%FS)	Burst Pressure
	(inH ₂ O)	(mbar)			
DP1	±1	±2.5	G	0.05	100x
DP2	±2	±5.0	G	0.05	100x
DP5	±5	±10	G	0.05	50x
DP10	±10	±25	G	0.05	20x
DP20	±20	±50	G	0.025	20x
DP30	±30	±75	G	0.025	15x
DP50	±50	±160	G	0.025	3x
DP150	±150	±350	G	0.025	3x
DP300	±300	±700	G	0.025	3x

* One year accuracy (including yearly stability) except DP1 and DP2 range which is 0.05%FS calibration accuracy and 0.05%FS yearly stability.

■ Environmental

Compensated Temperature: 14°F to 122°F (-10°C to 50°C)

Operating Temperature: 14°F to 122°F (-10°C to 50°C)

Storage Temperature: -4°F to 158°F (-20°C to 70°C)

Humidity: <95%

■ Pressure Connections

1/4NPT male, 1/4BSP male, M20X1.5 male

Other Connections available per request

■ Enclosure

Case material: SST

Wetted parts: 316L SS

Dimension: Ø1.3" x 4.84" (Ø33mm x 123mm)

Weight: 0.99 lb (0.4kg)

■ Warranty: 1 Year



Additel 160 Application

ORDERING INFORMATION

■ Model Number

ADT160 - 02 - GP300 - PSI - N

Model

Accuracy:

02-0.025% of full scale

05-0.05% of full scale

10-0.1% of full scale

Range type:

PSI - range by psi

BAR - range by bar

Pressure port type:

N - 1/4NPT male

N2 - 1/2NPT male

B - 1/4BSP male

M - M20 X 1.5 male


Pressure range P/N:

See pressure range table

■ Accessories included

NIST Traceable Calibration Certificate

■ Optional Accessories

Model number	Description	Picture
9060	Pressure module connection cable	

Corporate Headquarters

22865 Savi Ranch Parkway Ste F
Yorba Linda, CA 92887, USA

Phone: 714-998-6899

Fax: 714-998-6999

Email: sales@additel.com

Salt Lake City Office

802 Bamberger Dr, Suite C

American Fork, UT 84003, USA

Phone: 801-756-5570

Fax: 714-998-6999

Email: sales@additel.com